

Cove Powercore

Dimmable, linear LED fixture that provides an energy-efficient, low-maintenance alternative to traditional cove lighting in applications requiring white or solid-color light. With its low profile, rotating housing, flexible end-to-end locking power connectors, and range of colors and color temperatures, it is the perfect choice for a wide range of interior retail, exhibit, hospitality, and architectural settings.

Specifications:

Power Requirement: 100-240VAC, 50-60Hz

Watts: 15 Watts

Power Factor: 0.95 or greater at 120VAC

Source: High intensity LEDs

Color Temperature: 2800K and 4200K

Rated Life: 50,000 hours, 70% of original light output

Operating Temperature: -4°F to 122°F (-20°C to 50°C)

Size: 6" or 12" Linear

Beam Angle: Medium (50° x 50°), Forward-Throw Asymmetric (20° x 30° x 160°)



- Injection-molded plastic, gray finish
- Designed for common interior alcove applications, such as lobbies, atriums, schools, museums, malls, or other public spaces
- Product has adjustable aiming to tailor the illumination performance to the application.
- Certification UL / cUL, FCC Class B, CE
- LED Class Class 2 LED product
- Environment Dry Location, IP20
- Energy Efficiency California Title 24 Compliant






Product Order Code:

Order Code Example: LLT-10-PC-15-6-2800-100

| LLT | 10 | PC | 15 | | | |
|-----|----|----|----|---------------|--------------|------------|
| | | | | LENGTH | COLOR | VAC |
| | | | | 6 | 2800 | 100 |
| | | | | 12 | 4200 | 120 |
| | | | | | | 220-240 |

*Specifications may be customized to meet customer needs.

Accessories:

| | Item | Type | Size |
|---|--|----------|----------------|
|  | Leader Cable with terminator and strain relief | UL / cUL | 10 ft (3 m) |
| | | CE | 10 ft (3 m) |
|  | Wiring Compartment with terminator | UL / cUL | |
|  | Leader Cable with plug | UL / cUL | 8 ft (2.4 m) |
|  | Jumper Cable | UL / cUL | 1 ft (305 mm) |
| | | | 5 ft (1.5 m) |
| | | CE | 1 ft (305 mm) |
| | | | 5 ft (1.5 m) |
|  | Mounting Track | 25 / box | 4 ft (1219 mm) |