

Tele: 770-559-0750 Fax: 770-783-8097 www.LEDLightTech.com

## LED Light Tech<sup>™</sup> DS Wallpack

The DS Wallpack Series is designed for applications that require lighting with a long life and low maintenance requirement. With effective thermal management, corrosion-resistant, and die-cast aluminum enclosure with an architectural dark brown finish, the DS Wallpack provides glare free, uniform illumination while providing a safe and comfortable visual experience. This Wall Pack is available in 28 watts, 40 watts, 60 watts and 90watts. With superior 60%-90% energy savings, compared to

halogen lamp or a metal halide lamp, the DS wallpack achieves a luminous flux of 7200 lm and only consumes approximate 90 watts. High lumen output, energy-efficient optical control and easy universal installation features confirm this wallpack as the best choice for indoor and outdoor illumination.



## **SPECIFICATIONS:**

	28 Watt	40 Watt	60 Watt	90 Watt		
Input	28W, 100~277VAC, 0.3A	40W, 100~277VAC, 0.32A	55W, 100~277VAC, 0.47A	90W, 100~277VAC, 0.76A		
Lumens	2300 lm	3200 lm	4400 lm	7200 lm		
L70 lifetime	94,000h	72,000h	65,000h	52,000h		
Luminous efficacy	Typ. 80 Im/W					
ССТ	5000 K, 4000 K					
Color Accuracy	CRI >80, R9>10					
PF/THD	>0.92/<20%					

LLT-35-DS-Wallpack



9/29/2015



CONSTRUCTION & MATERIALS						
Туре	28W	40W	60W	90W		
Dimension (without visor)	363*195*230 mm (14.29*7.68*9.06")	363*195*230 mm (14.29*7.68*9.06")	465*244*230 mm (18.31*9.61*9.06")	465*244*230 mm (18.31*9.61*9.06")		
Housing	Die-cast aluminum					
Lens Type	Prismatic Glass					

ENVIRONMENTAL SYSTEM				
Work Environment	Indoor and outdoor use			
Operating Temperature	-20°C~50°C(-4~122°F)			
IP Rating	IP65			

ELECTRICAL SYSTEM					
Туре	28W	40W	60W	90W	
Input Voltage	100~277VAC, 0.3A	100~277VAC, 0.32A	100~277VAC, 0.47A	100~277VAC, 0.76A	
Off State Power	OW	OW	OW	OW	
Power Consumption	28W 40W		55W	90W	
THD	<20%				
Power Factor	>0.92				

LLT-35-DS-Wallpack



9/29/2015

LED Light Technology is a Certified Woman Owned Corporation qualifying for Corporate Diversity Purchasing Programs



Tele: 770-559-0750 Fax: 770-783-8097 www.LEDLightTech.com

OPTICAL SYSTEM						
Туре	28 W 40 W			60 W		90 W
Luminous Flux	2300 lm	2300 lm 3200 lm			0 lm	7200 lm
Luminous Efficacy	Typ. 80 lm/W					
Color Temperature	5000 K, 4000 K					
CRI	>80					
Lumen maintenance at 6000h	97.82%		97.49%		96.65%	

## **REGULATORY & VOLUNTARY QUALIFICATIONS**

Design Lights Consortium (40W, 60W, 90W)

ETL & cETL Listed

CA Title 24 Complaint (WPDS28)

LM79, LM80, Lighting Facts

Dark Sky Compliant



LLT-35-DS-Wallpack



9/29/2015

**LED Light Technology, LLC** 1004 Bay Tree Lane Duluth, Georgia 30097



Tele: 770-559-0750 Fax: 770-783-8097 www.LEDLightTech.com

## PRODUCT ORDER CODE:

Product Order Code Example: LLT-35-DSWP-90-50-00

LLT	35	DSWP	WATT	ССТ	CONTROL
			28=28W 40=40W	50=5000K	00=non-dimming
			60=60W 90=90W	40=4000K	10=1-10V Dimming

LLT-35-DS-Wallpack



9/29/2015