

# LED Light Tech™

## 75W LED Retrofit Kit for 200-250W HID

Upgrade your traditional HID fixtures to LED with LED Light Technology's 200-250 Watt HID replacement kit. Utilizing high efficiency Cree LEDs and reliable Meanwell drivers this state of the art retrofit kit will save you time, energy and money!

### SPECIFICATIONS:

- Fixture Type: Retrofit Kit
- LED Wattage: 75W
- Input Voltage: 100-277V, 347-480V
- Replaces: 200-250W HID
- LED Type: CREE
- Color Temp: 5500K | 4000K
- Lumens: 7,000
- LED L70 Life Hours: >100,000 @ 55°C
- Dimensions: HEAD – 6.75" x 4.5" x 3.0", DRIVER – 8.7" x 2.4" x 1.5"
- Color Rendering Index (CRI): >70
- Operating Temperature: -40°C to +60°C
- Lifetime Rating: >100,000 hours @ 55°C
- Beam Angle: 115°
- Protection: Short circuit / Over-current / Over-voltage / Over-temperature protection with auto-recovery
- Mounting: Bracket mounting system or custom-fabricated plates to fit most any HID fixture.
- Certification: ETL (UL-1598-C) & cETL (ANSI/UL 1598/CAN/CSA C22.2)
- 10/5 Warranty: 10-year warranty on components, including the LEDs, fan heat sink, etc. and a 5-year warranty on the LED Driver. See full warranty on website.



**PRODUCT ORDER CODE:**

Product Order Code Example: LLT-50-250Retro-75-5-277-H

LLT	50	250Retro	75				
				<b>CCT</b>	<b>Driver Type</b>	<b>Mount</b>	<b>Options</b>
				5= 5000K (Standard)	277= 100-277V, 150W Driver	H=Horizontal	SP277= Surge Protector 20kA, 100-277V
				4= 4000K (Special Order)	277D= 100-277V, 150W Dimmable Driver	V=Vertical	SP480=Surge Protector 20kA, 347-480V
					480= 347- 480V 150W Driver	FTP= Flex Trim Plate with Extension Tabs	PC120=Photo Cell -120V Photo
							PC277=PhotoCell 208-277V
							PC120R= PhotoCell 120V- Rotatable