

LED Light Tech™ 206W LED Retrofit Kit for 600W HID

Upgrade your traditional HID fixtures to LED with LED Light Technology's 600 Watt HID replacement kit. Utilizing high efficiency Cree LEDs and reliable Meanwell drivers this state of the art retrofit kit will save you time, energy and money!

SPECIFICATIONS:

- Fixture Type: Retrofit Kit
- LED Wattage: 206W
- Input Voltage: 100-277V, 347-480V
- Replaces: 600W HID
- LED Type: CREE
- Color Temp: 5500K | 4000K
- Lumens: 20,500
- LED L70 Life Hours: >100,000 @ 55°C
- Dimensions: head dimensions – 6.75" x 4.5" x 3.0", Drivers dimensions – 8.7" x 2.4" x 1.5"
- Color Rendering Index (CRI): >74
- Operating Temperature: -40°C to +60°C
- Lifetime Rating: >100,000 hours @ 55°C
- Beam Angle: 125° (Optional Optics: 56° | Type III | Type V)
- Standard Driver: DV185-277, 185W Driver
- Protection: Short circuit / Over-current / Over-voltage / Over-temperature protection with auto-recovery
- Mounting: Bracket mounting system or custom-fabricated plates to fit most any HID fixture.
- Certification: ETL (UL-1598-C) & cETL (ANSI/UL 1598/CAN/CSA C22.2)
- 10/5 Warranty: 10-year warranty on components, including the LEDs, fan heat sink, etc. and a 5-year warranty on the LED Driver. See full warranty on website.



PRODUCT ORDER CODE:

Product Order Code Example: LLT-50-600Retro-206-5-277-H-X-FTP

LLT	50	600Retro	206					
				CCT	Driver Type	Mount	Options	Optional Mounting Plate
				5= 5000K (Standard)	277= 100-277V, 150W Driver	H=Horizontal	SP277= Surge Protector 20kA, 100-277V	FTP= Flex Trim Plate
				4= 4000K (Special Order)	277D= 100-277V, 150W Dimmable Driver	V=Vertical	SP480=Surge Protector 20kA, 347-480V	FTP-T= Flex Trim Plate with Extension Tabs
					480= 347-480V 150W Driver		PC120=Photo Cell -120V Photo	CP= Custom Plate
							PC277=PhotoCell 208-277V	
							PC120R= PhotoCell 120V-Rotatable	

